

Solvent Recovery Systems

ECONOMY LINE: Series VRA

For medium and large distillation rates

- Profitable from 100 l/day, low investment costs
- Short lead time
- 250 to 4,000 litres of volume
- Fully automatic operation, 24/7
- Advanced clean technology, closed system
- Integrated heating and vacuum unit
- Water-cooled vapour condenser
- Explosion-proof according to ATEX Directive 2014/34/EU
- Made in Germany



Photo: VRA-250 with optional equipment



LÖMI GmbH
Baumschulweg 1
63762 Grossostheim
Germany

Tel.: +49 6026 99622-0
Fax: +49 6026 99622-30

Solvent Recovery Systems

Model	VRA-250	VRA-400	VRA-800	VRA-1200
Distillation rate, depending on solvent, water content and type and degree of pollution	40 – 100 l/h ^{*1}	60 – 140 l/h ^{*1}	80 – 250 l/h ^{*1}	120 – 300 l/h ^{*1}
Operating vacuum, medium water at 15 °C	max. 33 mbar [*]	max. 33 mbar [*]	max. 33 mbar [*]	max. 33 mbar [*]
Heating temperature max.	180 °C	180 °C	180 °C	180 °C
Marking, ATEX 2014/34/EU	⊕ II 2G Exh IIA T3 Gb ²	⊕ II 2G Exh IIA T3 Gb ²	⊕ II 2G Exh IIA T3 Gb ²	⊕ II 2G Exh IIA T3 Gb ²
Width	1500 mm	1850 mm	2000 mm	2250 mm
Height	2650 mm	2750 mm	2850 mm	3100 mm
Depth	910 mm	1400 mm	1550 mm	1800 (+800) mm
Empty weight approx.	530 kg	1000 kg	1100 kg	1550 kg
Model	VRA-1600	VRA-2000	VRA-3000	VRA-4000
Distillation rate, depending on solvent, water content and type and degree of pollution	200 – 400 l/h ^{*1}	300 – 500 l/h ^{*1}	400 – 1000 l/h ^{*1}	400 – 1300 l/h ^{*1}
Operating vacuum, medium water at 15 °C	max. 33 mbar [*]	max. 33 mbar [*]	max. 33 mbar [*]	max. 33 mbar [*]
Heating temperature max.	180 °C	180 °C	180 °C	180 °C
Marking, ATEX 2014/34/EU	⊕ II 2G Exh IIA T3 Gb ²	⊕ II 2G Exh IIA T3 Gb ²	⊕ II 2G Exh IIA T3 Gb ²	⊕ II 2G Exh IIA T3 Gb ²
Width	2250 mm	2250 mm	2600 mm	2600 mm
Height	3450 mm	3800 mm	4300 mm	4400 mm
Depth	1800 (+800) mm	1800 (+800) mm	2150 (+950) mm	2150 (+950) mm
Empty weight approx.	1700 kg	2100 kg	3000 kg	3800 kg

Technical specifications are subject to alteration and are to be considered as an orientation, since each system is engineered and manufactured specifically according to your requirements. Other sizes available on request.

* Values can only be guaranteed after testing your original waste product.

¹ Non-binding approximate values for liquid-solid distillation of organic solvents with a maximum boiling point of 210 °C and a maximum solids content of 5 %.

² Optionally available with ATEX Marking ⊕ II 2G Exh IIB T3 Gb or certified according to IECEx System.



LÖMI Process Technology

Excellence in Solvent Recovery and PIM Debinding since 1991

www.loemi.com